



◆ SPECIFICATION

| Model NO. | IP3LDAHL200 |
|-------------------------|--|
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Resolution | 2MP 1080P |
| Effective Pixels | 1945(H)*1097(V) |
| Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/30-1/10000Sec |
| Minimun Illumination | 0.005Lux |
| S/N Ratio | ≥52dB |
| Scanning System | Progressive |
| Video Output | Network |
| Reset Button | Optional |
| Lens | |
| Focus Length | 2.7-13.5mm |
| Focus Control | Auto |
| Lens Type | Auto |
| Pixels | 3MP |
| Night Vision | |
| Infrared LED | 42μ x 4PCS |
| Infrared Distance | 30M |
| IR Status | Auto Control |
| IR Power On | Auto Control |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |

| | |
|------------------------|--|
| Wireless | / |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| ONVIF | Support ONVIF 2.4(Profile S/T/G) |
| P2P | YES, Support QR Code |
| POE | Internal, Support IEEE 802.3af |
| Video Delay | 0.3S (Within the Lan) |
| Main Stream 1 | 2304*1296@20fps |
| Main Stream 2 | 1920*1080@30fps |
| Main Stream 3 | 1280*720@30fps |
| Sub Stream 1 | 720*480@20fps 720*480@30fps |
| Sub Stream 2 | / |
| Sub Stream 3 | / |
| Tri Stream | 352*288@20fps 352*288@30fps |
| IE Brower | IE8-11, Google Chrome, Firefox, Mac Safari |
| Smart Phone | iPhone, iPad, Android, Android Pad |
| AI Function | |
| Intelligent Analysis | Intrusion Detetion, Line Cross Detetion, Loiter Detetion, People Gather Detecion |
| Recognition | Face Detection and Recognition Number of faces per frame: 32 Capture rate: >99.5% Repeat capture rate: <15% False capture rate: <0.5% Number of supported faces: 10,000 Minimum detection of face pixels: 25*25 Maximum detection of face pixels: 300*300 |
| Camera Features | |
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering, HLC, Distortion |
| Corridor Pattern | / |
| Defog Mode | Support |
| ROI | Support |
| BLC | Support |
| WDR | HDR: 120dB |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR/CMS/Web |

| | |
|-----------------------|---|
| Language | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese |
| Interface | |
| Audio | Audio IN/OUT by Line |
| Alarm | 1 Channel Input/Output |
| SD Card Slot | Support Max 512GB |
| RS485 | Support |
| General | |
| Housing | IP67 |
| Anti-cut Bracket | NO |
| IR Cut Filter | YES |
| Operation Temperature | -20°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%,950mA |
| Dimension | φ159 x 132(H)mm |
| Weight | 1.4Kgs |

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com