



◆ SPECIFICATION

| | |
|-------------------------|---|
| Model NO. | NVRC421PKM4FE800R |
| Package | |
| NVR | 1x NVRC421PK |
| Camera | 4 x IPR25FE800 |
| Cable | 4x 20m CAT5e Cable |
| Mouse | 1xUSB 2.0 Mouse |
| Hard Disk | No |
| Adaptor | DC52V/1.25A |
| Weight | 6.8kg/SET |
| Camera Model | IPR25FE800 |
| Image Sensor | 1/2.5" High-resolution CMOS Sensor |
| Resolution | 8MP |
| Effective Pixels | 2704(H)*1950(V) |
| Compression | H.265 |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec |
| Minimum Illumination | 0.01Lux |
| S/N Ratio | ≥52dB |
| Scanning System | Progressive |
| Video Output | Network |
| Reset Button | Optional |
| Lens | |
| Focus Length | 3.6mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Pixels | 5MP |
| Night Vision | |

| | |
|------------------------|--|
| Infrared LED | 14μ x 20PCS |
| Infrared Distance | 25M |
| IR Status | Auto Control |
| IR Power On | Auto Control |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Wireless | / |
| Protocol | TCP/IP,ICMP,RTP,RTSP,RTCP |
| ONVIF | / |
| P2P | / |
| POE | Yes, Support IEEE 802.3af |
| Video Delay | 0.3S (Within the Lan) |
| Main Stream 1 | 3840x2160@15fps |
| Main Stream 2 | / |
| Main Stream 3 | / |
| Sub Stream 1 | 1280x720@15fps |
| Sub Stream 2 | / |
| Sub Stream 3 | / |
| Tri Stream | / |
| IE Brower | / |
| Smart Phone | / |
| Camera Features | |
| Day/Night | Color/ B&W (IR-CUT) |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, White Balance, FLK(Flicker Control) |
| Starlight | / |
| Corridor Pattern | / |
| Defog Mode | / |
| ROI | / |
| BLC | YES |
| HDR | / |
| WDR | NO |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |
| Recording Mode | NVR |
| Language | / |
| Interface | |
| Audio | / |
| Alarm | / |
| SD Card Slot | / |
| RS485 | / |
| General | |

| | |
|----------------------------|---|
| Housing | Metal , IP67 |
| Anti-cut Bracket | YES |
| IR Cut Filter | YES |
| Operation Temperature | -20℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%, 950mA |
| Dimension | 157(W) x 70(H) x 66(D)mm |
| Weight | 650g |
| Model | NVRC421PK |
| System | |
| Main Processor | ARM Cortex A7 Processor |
| Operating System | Embedded LINUX |
| Video | |
| Input | 9CH (3840×2160, 2592×1944, 2048×1536, 1920×1080, 1280×960, 1280×720, etc) |
| Output | 1 VGA, 1 HD |
| Audio | |
| Input | 1 Port RCA |
| Output | 1 Port RCA(Linear, 1kΩ) |
| Audio Bit Rate | 64kbps |
| Audio Compression standard | G711u, G711a, ADPCM_DVI4 |
| Alarm | |
| Sensor Input | 4 |
| Output | 1 |
| Motion Detection | 9 Channel, MD Zones: 396 (22 × 18) |
| Trigger Events | Recording, Email, FTP, Snapshot, Buzzer and Screen Tips, alarm output |
| Display | |
| HD Output1 | Resolution:4K (3840 × 2160)/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz |
| HD Output2 | / |
| VGA | Resolution:1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz |
| Display Split | 9CHxD1/8CHxD1/4CHxD1/1CHx1080P/1CHx3MP/1CHx4MP/1CHx5MP/1CHx4k |
| Digital Zoom | YES |
| OSD | Camera Title, Time, Recording, Motion Detection, Event Alarm |
| Recording | |
| Video Compression | H265/H264/H265+/H264+ |
| Resolution | 4k(3840×2160),5MP(2592×1944),4MP(2688×1520/2560×1440),3MP(2048×1536), 1080P(1920×1080),960P(1280×960),720P(1280×720),D1 (720×576/720×480) |

| | |
|------------------------------|---|
| Record Rate | PAL :4k@10×25fp,5MP@14×25fp,4MP@16×25fp,3MP@16×25fp,1080P@16×25fp, 960P@16×25fp,720P@16×25fp, D1@16×25fp NTSC: 4k@10×30fp,5MP@14×30fp,4MP@16×30fp,3MP@16×30fp,1080P@16×30fp, 960P@16×30fp, 720P@16×30fp, D1@16×30fp |
| Record Mode | Manual\Timer\Motion Detection\ Alarm\Motion and Alarm\Smart Alarm |
| Playback & Backup | |
| Local Sync Playback | 1CH 4K@30fps, 1CH 5MP@30fps,2CH 4MP@30fps, 2CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps |
| Decode Capability | 4CH 1080P(1920x1080)@30fps |
| Remote Sync Playback | YES |
| Search Mode | ALL, Channel, Manual, Time, Date, Motion Detection,Event Alarm,Tag search |
| Playback Functions | Play, Pause, Stop, Rewind, Fast play, Slow Play, Full Screen, Frame Play ,Frame Rewind, Digital Zoom,tag,clip |
| Backup Mode | USB Device/Network |
| Network | |
| Interface | 8 x RJ45 (10M/100M Adaptive Ethernet Interface)+1xRJ45 10M/100M/1000M Adaptive Ethernet Interface |
| Incoming Bandwidth | 100MB |
| Network Functions | TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, DHCP, FTP, DDNS, RTSP, RTCP, p2p,PPPOE |
| Onvif Version | Support Onvif 2.8 |
| Web Browser | IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53) |
| CMS Software | Support Windows 7/ Windows 8/Windows 10/MAC OS |
| Cloud Support(P2P) | Yes |
| Smart Phone | iPhone, iPad, Android, Android Pad |
| POE | 8 x Independent 100Mbps POE Network Interfaces(Output PowerAT mode 30W, AF mode 15W per Interface), 45/78 line order, Total Power Output \cong 100W, Support Plug and Play, Support network cable extended mode Max. 200M |
| WIFI | / |
| Storage | |
| Interface Type | 1 SATA Hard Disk Interface (2.5"/3.5" SATA) |
| Capacity | Up to 8TB capacity |
| eSATA | / |
| General | |
| Language | Traditional Chinese, Simplified Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek, Vietnamese, Janpenes |
| USB Interface | 2 USB 2.0 Interfaces |
| RS485 | / |
| Power Supply | DC 52V/2500mA \leq 10W (Without Hard Disk and POE) |
| Working Environment | -10~55℃/10~90% |
| Dimension(W×D×H) | 260*215*43(mm) |
| Weight | 2.0KG (without HDD) |

Cantonk(guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com