**Cantonk** "Reliable Digital Security Products Manufacturer"



♦ SPECIFICATION

Note BNQ 55(pr) 2.5 Sip. SM 20 (pr) 2.5 Sip. 44//2M @ 30 (pr) 2.5 Sip. 54 (pr) 44//52           Image Benor         1/2.8" SOMY Starvis Back illuminated CMOS sensor           Image Benor         94//ATSC           Image Benor         94//ATSC           Scinning System         PAL/NTSC           Electronic Shutter         Auto           Scinning System         Progressive Scan           Lens         2.7:13.5mm Motor Zoom           Focus Control         Auto           Night Vision         VES           Infared LED         45530/-2           Light Distance         up to 30m           R Status         AGC auto control           Camero         Focus Control           Camero         Yes           Starlight         /           Day/Might         Color           OSD Menu         Yes           VIC         Yes           Mitte Balance         AUTO / MANUAL           Gain Control         AUTO           Camero         Yes           Mitte Balance         AUTO / MANUAL           Gain Control         AUTO           Gareerol	Model NO.	KLCBHTC8005XESLW
Inage Sensor         1/2.8" SONY Starvis Back-illuminated CMOS sensor           image Resolution         8M.3840*2160 5M.2592*1944 4M.2560*1440 2M.1920*1080           TV System         PAL/NTSC           Electronic Shutter         Auto           Scanning System         Progressive Scan           Lens	Video Output Mode	4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps,
Image Resolution         8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080           TV System         PAL/NTSC           Electonic Shutter         Auto           Scanning System         Progressive Scan           Lens	Camera	
TV System     PAL/NTSC       Electronic Shutter     Auto       Scanning System     Progressive Scan       Lens	Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Electronic Shutter         Auto           Scanning System         Progressive Scan           Lens	Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
Scanning System     Progressive Scan       Lens	TV System	PAL/NTSC
Lens         Focus Length       2.7-13.5mm Motor Zoom         Focus Control       Auto         Infrared XED       Auto         Night Vision       Infrared XED         Infrared XED       4545Ux2         Uight Distance       up to 30m         IR Cut Filter       YES         Infrared XED       46C auto control         Comerco       /         Features       /         Startight       /         Day/Night       Color         OSD Menu       YES         WOR       YES         UTC       YES         Noise Reduction       3DNR         White Balance       AUTO / MANUAL         Gain Control       AUTO         Cenercol	Electronic Shutter	Auto
Focus Length         2.7-13.5mm Motor Zoom           Focus Control         Auto           Lens Type         Auto           Night Vision         Infrared LED           IR Cut Filter         YES           Infrared LED         4545U×2           Light Distance         up to 30m           IR Status         AGC auto control           Camero	Scanning System	Progressive Scan
Focus Control     Auto       Focus Control     Auto       Night Vision     Instance       IR Cut Filter     YES       Infrared LED     4545U×2       Light Distance     up to 30m       IR Status     AGC auto control       Camera     Genera       Features     /       Starlight     /       Day/Night     Color       OSD Menu     YES       UTC     YES       UTC     YES       WNR     YES       UTC     YES       UTC     AUTO / MANUAL       Gain Control     AUTO       Gain Control     AUTO       General	Lens	
Lens Type     Auto       Night Vision        IR Cut Filter     YES       Infrared LED     4545Ux2       Light Distance     up to 30m       IR Status     AGC auto control       Camera        Features        Starlight     /       Day/Night     Color       OSD Menu     YES       WDR     YES       UTC     YES       UTC     YES       Woke Reduction     3DNR       Starlight     AUTO / MANUAL       Gain Control     AUTO       Ganeral        PowerSource     -10°C * 460°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     C 136 x 148(H)mm	Focus Length	2.7-13.5mm Motor Zoom
Night Vision         IR Cut Filter       YES         Infrared LED       4545U+2         Light Distance       up to 30m         IR Status       AGC auto control         Camero       Fectures         Fectures       /         Starlight       /         Day/Night       Color         OSD Menu       YES         WDR       YES         UTC       YES         Noise Reduction       3DNR         White Balance       AUTO / MANUAL         Gain Control       AUTO         Generol	Focus Control	Auto
IR Cut Filter VES Infrared LED 4545U×2 Light Distance up to 30m IR Status AGC auto control Commerce Features Starlight / / Day/Night Color OSD Menu YES WDR YES WDR YES WDR YES UTC YES Noise Reduction 30NR White Balance AUTO / MANUAL Gain Control AUTO Cenercel Housing IP67 Bracket NO Operation Temperature -20°C ~ 460°C RH95% Max Power Source DC12V±10%,550mA Dimension C 136 x 148(H)mm	Lens Type	Auto
Infrared LED 4545U×2 Light Distance up to 30m IR Status AGC auto control Camera Features Starlight / Day/Night Color OSD Menu YES WDR VES WDR YES UTC YES Noise Reduction 3DNR White Balance AUTO / MANUAL Gain Control AUTO Ceneral Housing IP67 Bracket NO Operation Temperature -10°C ~ 460°C RH95% Max Storage Temperature -20°C ~ 460°C RH95% Max	Night Vision	
Light Distance     up to 30m       IR Status     AGC auto control       Camero Features     //       Starlight     //       Day/Night     Color       OSD Menu     YES       WDR     YES       UTC     YES       UTC     YES       Noise Reduction     3DNR       White Balance     AUTO / MANUAL       Gain Control     AUTO       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     C 136 x 148(H)mm	IR Cut Filter	YES
IR Status AGC auto control Camera Features Starlight / Day/Night Color OSD Menu YES WDR YES WDR YES UTC YES Noise Reduction 3DNR White Balance AUTO / MANUAL Gain Control AUTO General Housing IP67 Bracket N0 Operation Temperature -20°C ~ +60°C RH95% Max Power Source DC12V±10%,550mA Dimension C 136 x 148(H)mm	Infrared LED	4545U×2
Camera         Features         Starlight         Jay/Night         Color         OSD Menu         VES         WDR         VES         WDR         VES         UTC         Noise Reduction         3DNR         White Balance         AUTO / MANUAL         Gain Control         AUTO         General         Housing         IP67         Bracket         NO         Operation Temperature         -20°C ~ +60°C RH95% Max         Storage Temperature         Power Source       DC12V±10%,550mA         Dimension       4° 136 × 148(H)mm	Light Distance	up to 30m
Features         Starlight       /         Day/Night       Color         OSD Menu       YES         WDR       YES         UTC       YES         UTC       YES         Noise Reduction       3DNR         White Balance       AUTO / MANUAL         Gain Control       AUTO         Housing       IP67         Bracket       NO         Operation Temperature       -10°C ~ +60°C RH95% Max         Storage Temperature       -20°C ~ +60°C RH95% Max         Power Source       DC12V±10%,550mA         Dimension       4'136 x 148(H)mm	IR Status	AGC auto control
Starlight     /       Day/Night     Color       OSD Menu     YES       WDR     YES       UTC     YES       UTC     YES       Noise Reduction     3DNR       White Balance     AUTO / MANUAL       Gain Control     AUTO       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     C 136 x 148(H)mm		
OSD Menu     YES       WDR     YES       WDR     YES       UTC     YES       Noise Reduction     3DNR       White Balance     AUTO / MANUAL       Gain Control     AUTO       General     IP67       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA	Starlight	/
WDR     YES       UTC     YES       Noise Reduction     3DNR       White Balance     AUTO / MANUAL       Gain Control     AUTO       General     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     € 136 x 148(H)mm	Day/Night	Color
UTC     YES       Noise Reduction     3DNR       White Balance     AUTO / MANUAL       Gain Control     AUTO       General     IP67       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     ¢ 136 x 148(H)mm	OSD Menu	YES
Noise Reduction       3DNR         White Balance       AUTO / MANUAL         Gain Control       AUTO         General       IP67         Housing       IP67         Bracket       NO         Operation Temperature       -10°C ~ +60°C RH95% Max         Storage Temperature       -20°C ~ +60°C RH95% Max         Power Source       DC12V±10%,550mA         Dimension       € 136 x 148(H)mm	WDR	YES
White Balance     AUTO / MANUAL       Gain Control     AUTO       General     Housing       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     & 136 x 148(H)mm	UTC	YES
Gain Control     AUTO       General     IP67       Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     ¢ 136 x 148(H)mm	Noise Reduction	3DNR
Ceneral         Housing       IP67         Bracket       NO         Operation Temperature       -10°C ~ +60°C RH95% Max         Storage Temperature       -20°C ~ +60°C RH95% Max         Power Source       DC12V±10%,550mA         Dimension       ¢ 136 x 148(H)mm	White Balance	AUTO / MANUAL
Housing     IP67       Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     ¢ 136 x 148(H)mm	Gain Control	AUTO
Bracket     NO       Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     ¢ 136 x 148(H)mm	General	
Operation Temperature     -10°C ~ +60°C RH95% Max       Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     & 136 x 148(H)mm	Housing	IP67
Storage Temperature     -20°C ~ +60°C RH95% Max       Power Source     DC12V±10%,550mA       Dimension     C 136 x 148(H)mm	Bracket	NO
Power Source DC12V±10%,550mA Dimension	Operation Temperature	-10°C ~ +60°C RH95% Max
Dimension C 136 x 148(H)mm	Storage Temperature	-20℃ ~ +60℃ RH95% Max
	Power Source	DC12V±10%,550mA
Weight 1.7Kgs	Dimension	¢ 136 x 148(H)mm
	Weight	1.7Kgs

 Add.
 2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

 Tel. No.: +86 20 66217288
 Fax No.: +86 20 66217166
 Homepage: http://www.cantonk.com
 Email: info@cantonk.com