



◆ SPECIFICATION

Model NO.	KLCAHD400ESL
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Scanning System	Progressive Scan
Lens	
Focus Length	Board Lens 6mm
Focus Control	Fixed
Lens Type	Fixed
Night Vision	
IR Cut Filter	YES
Infrared LED	42μ x2PCS
Infrared Distance	30M
IR Status	AGC Auto Control
Camera Features	
Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	AUTO / MANUAL
White Balance	3DNR
Gain Control	AUTO
General	
Housing	IP67
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,500mA
Dimension	∅ 115 x 113(H) mm
Weight	800g

Cantontk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantontk.com> Email: info@cantontk.com