



◆ SPECIFICATION

|                        |   |
|------------------------|---|
| Model NO.              | KBBQ90HD4005XESL  |
| Video Output Mode      | EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps;<br>AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps; |
| <b>Camera</b>          |   |
| Image Sensor           | 1/2.8" SONY Starvis Back-illuminated CMOS sensor  |
| Image Resolution       | 8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080   |
| TV System              | PAL/NTSC  |
| Electronic Shutter     | Auto  |
| Scanning System        | Progressive Scan  |
| <b>Lens</b>            |   |
| Focus Length           | 2.7-13.5mm Motor Zoom   |
| Focus Control          | Auto  |
| Lens Type              | Auto  |
| <b>Night Vision</b>    |   |
| IR Cut Filter          | YES   |
| Infrared LED           | 42μ x6PCS   |
| Infrared Distance      | 60M   |
| IR Status              | AGC Auto Control  |
| <b>Camera Features</b> |   |
| Starlight              | /   |
| Day/Night              | YES   |
| OSD Menu               | YES   |
| WDR                    | YES   |
| UTC                    | YES   |
| Noise Reduction        | 3DNR  |
| White Balance          | AUTO / MANUAL   |
| Gain Control           | AUTO  |
| <b>General</b>         |   |
| Housing                | IP67  |
| Bracket                | YES   |
| Operation Temperature  | -10℃ ~ +60℃ RH95% Max   |
| Storage Temperature    | -20℃ ~ +60℃ RH95% Max   |
| Power Source           | DC12V±10%,900mA   |
| Dimension              | 211(W) x 92(H) x 90(D)mm  |
| Weight                 | Weight: 1.4Kgs  |

Cantonek (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA  
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonek.com> Email: [info@cantonek.com](mailto:info@cantonek.com)