



◆ SPECIFICATION

Model NO.	KLCAHD4005XESL
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI: 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 4M/2M@30fps/25fps;
Camera	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080
TV System	PAL/NTSC
Electronic Shutter	Auto
Scanning System	Progressive Scan
Lens	
Focus Length	2.7-13.5mm Motor Zoom
Focus Control	Auto
Lens Type	Auto
Night Vision	
IR Cut Filter	YES
Infrared LED	42μ x2PCS
Infrared Distance	30M
IR Status	AGC Auto Control
Camera Features	
Starlight	/
Day/Night	YES
OSD Menu	YES
WDR	YES
UTC	YES
Noise Reduction	3DNR
White Balance	AUTO / MANUAL
Gain Control	AUTO
General	
Housing	IP67
Bracket	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,500mA
Dimension	∅ 115 x 113(H) mm
Weight	800g

Cantonek (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonek.com> Email: info@cantonek.com