

## ♦ SPECIFICATION

Model NO.	KMBAHD800ES	
Video Output Mode	EX-SDI: 8M@15fps, 4M/2M@30fps/25fps; HD-SDI: 2M@30fps/25fps; AHD/TVI/CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps	
Camera		
Image Sensor	1/2.8" SONY CMOS sensor	
Image Resolution	8M:3840*2160 4M:2560*1440 2M:1920*1080	
Electronic Shutter	PAL/NTSC	
TV System	Auto	
Scanning System	Progressive Scan	
Lens		
Focus Length	Board Lens 6mm	
Focus Control	Fixed	
Lens Type	Fixed	
Night Vision		
IR Cut Filter	YES	
Infrared LED	42μ x4PCS	
Infrared Distance	40M	
IR Status	AGC Auto Control	
Camera Features		
Starlight	/	
Day/Night	YES	
OSD Menu	YES	
WDR	YES	
UTC	YES	
Noise Reduction	3DNR	
White Balance	AUTO / MANUAL	
Gain Control	AUTO	
General		

Housing	IP67
Bracket	YES
Operation Temperature	-10°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%,750mA
Dimension	170(W) x 110(H) x 101(D)mm
Weight	1.65Kgs (With bracket)

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: http://www.cantonk.com Email: info@cantonk.com