



◆ SPECIFICATION

Model NO.	S300GS	S300GD
Basic Parameters		
Driver Signal	12V	
Driver Voltage	24V	
Movement	Single	Dual
Passing Speed	35 Persons/Min	
Traffic	Unidirectional/Bidirectional	
Open & Close Time	0.5-1s	
Material	304 Stainless	
Channel Width	≤600mm	
Swing Arm	270mm/acrylic	
Card Reader	Support	
Counting People	Optional	
Illegal infiltration	Support	
Anti-pinch	Infrared/Mechanical	
Infrared	3 Pairs	
Interface		
RS485	RS485 electrical standard,communication distance: <1200 meters	
Input Port	Switch Signal(NO NC COM)	
Network Port	Optional	
General Specification		
Power	220V±10% 50Hz 110V±10% 60Hz(optional)	
Working Temperature	-30℃~60℃/10~95%	
Device Size	1200*300*980mm	
Package Size	126*68*116	126*98*116

Package Weight	257.4KGs	371.8KGs
----------------	----------	----------

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com