



◆ SPECIFICATION

| Model NO. | KHKHL200W |
|-------------------------|--|
| Camera | |
| Image Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Resolution | 2MP 1080P |
| Effective Pixels | 1945(H)*1097(V) |
| Compression | H.264/H.264+/H.265/H.265+/JPEG/AVI/MJPEG |
| TV System | PAL/NTSC |
| Electronic Shutter Time | Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec |
| Minimum Illumination | 0.005Lux |
| S/N Ratio | ≥52dB |
| Scanning System | Progressive |
| Video Output | Network |
| Reset Button | \ |
| LENS Type | |
| Focus Length | Board Lens 3.7mm |
| Focus Control | Fixed |
| Lens Type | Fixed |
| Pixels | 2MP |
| Night Vision | |
| Infrared LED | / |
| Infrared Distance | / |
| IR Status | / |

| | |
|------------------------|---|
| IR Power On | / |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Protocol | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| ONVIF | Support ONVIF 2.4(Profile S) |
| P2P | YES, Support QR Code |
| POE | Optional(External POE But Without Audio and Alarm Functions), Support IEEE 802.3af |
| Video Delay | 0.3S (Within the Lan) |
| Main Stream 1 | 1920*1080@30fps |
| Main Stream 2 | 1280*720@25fps |
| Main Stream 3 | / |
| Sub Stream 1 | 720*480@30fps |
| Sub Stream 2 | / |
| Sub Stream 3 | / |
| Tri Stream | 352*288@30fps |
| IE Brower | IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari(lower than version 12) |
| Smart Phone | iPhone, iPad, Android, Android Pad |
| Wireless | |
| Antena | 2.5dbi |
| Hotspot | / |
| Wi-Fi | Wi-Fi(IEEE802.11b/g/n),2.4Ghz |
| WIFI Range | No obstacles 100m Max. |
| Camera Features | |
| Day/Night | Color |
| Image Config | Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control) |
| Corridor Pattern | Support |
| ROI | / |
| Defog Mode | Support |
| BLC | Support |
| WDR | DWDR: 50dB |
| Motion Detection | Support |
| Privacy Masking | 3 Rectangular Zone |

| | |
|------------------|---|
| Recording Mode | NVR/VMS/Web/SD Card |
| Language | Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands, Czech, Vietnamese |
| Interface | |
| Audio | Audio IN/OUT by Line(3.5mm audio interface) |
| Alarm | 1channel Input(3.3V~20V) |
| SD Card Slot | support 512G Micro SD |
| RS485 | / |

General

| | |
|-----------------------|-------------------------|
| Housing | Metal |
| Anti-cut Bracket | NO |
| IR Cut Filter | NO |
| Operation Temperature | -20°C ~ +60°C RH95% Max |
| Storage Temperature | -20°C ~ +60°C RH95% Max |
| Power Source | DC12V±10%, 350mA |
| Dimension | 36(W) x 36(H) x33(D)mm |
| Weight | 300g |

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com