



◆ SPECIFICATION

Model	PTDA4XHHL200
Camera	
Image Sensor	1/2.9" SONY Low Illumination 2.1MP CMOS Sensor
Horizontal Resolution	2MP
Compression	H.264/H.265
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	25°/s
Horizontal Rotation Range	0°~355°
Tilt Rotation Speed	20°/s
Tilt Rotation Range	0°~70°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	2.8mm-12mm
Focus Control	4X Optical Zoom
Night Vision	
Infrared LED	35μx4PCS
IR Range	45m
Day-night mode	AUTO
Network	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	2304*1296@20fps
Main Stream2	1920*1080@30fps
Sub Stream1	800*448@30fps
Sub Stream2	704*576@30fps
Sub Stream3	640*360@30fps
Sub Stream4	352*288@30fps
Interface	
Audio	Optional
Alarm	/
SD Card Slot	/
POE	Optional
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -15°~ +60°
Operating Humidity	≤90% Non Condensing

Power	DC12V 2A
Lightning Protection	Transient voltage 6000V
Dimension	14x14x13(cm)
Weight	1.1Kgs

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com