



◆ SPECIFICATION

Model	RT2418	
Power	Power Adapter Voltage	Input 100-240V/AC 50/60Hz
	The maximum power supply machine	370W
Protection level	Mould	+4KV
	Differential mode	+1KV
Network Connector	Network Port	1~24 port: :10/100Mbps PoE Ethernet port 25~28 port:10/100/1000Mbps WAN1/WAN2 port
	Transmission Distance	1~24 port: Recommended distance is 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch	Network Standard	IEEE802.3/10BASE-T Ethernet
		IEEE802.3u/100BASE-TX Ethernet
		IEEE802.3ab 1000BASE-T Ethernet
	Maximum Frame Size	1536 Bytes
	MAC address list	2K
Power Over Ethernet	PoE Power Supply Type	End-Span(4/5+;7/8-)
	PoE Power Consumption	at, (every port)
LED Status Indicator	POE Ethernet	POE: 24 green light indicates that the POE is power on
		Ethernet: 24 yellow light indicates that the Ethernet Link and Act
Environmental	Working temperature	0°C~50°C
	Working humidity	0%-90% non-condensing
	Storage temperature	-40°C~85°C
	Storage Humidity	0%-90% RH non-condensing
Mechanical	Dimension (L x W x H) mm	441*300*44
	Material	SECC
	Color	Dark gray
Stability	MTBF	>30000h

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288

Fax No.: +86 20 66217166

Homepage: <http://www.cantonk.com>

Email: [info@cantonk.com](mailto:info@cantonk.com)