



◆ SPECIFICATION

| Model NO. | KBCW60HTC200FE | KBCW60HTC200F | KBCW60HTC200ESL |
|-------------------|-----------------------------|-----------------------------|-----------------------------|
| Video Output Mode | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps | AHD/TVI/CVI: 2M@30fps/25fps |

Camera

| | | | |
|--------------------|------------------|--------------------|--|
| Image Sensor | 1/3" CMOS Sensor | 1/2.9" CMOS Sensor | 1/2.8" SONY Starvis Back-illuminated CMOS Sensor |
| Image Resolution | 2M:1920*1080 | 2M:1920*1080 | 2M:1920*1080 |
| TV System | PAL/NTSC | PAL/NTSC | PAL/NTSC |
| Electronic Shutter | Auto | Auto | Auto |
| Scanning System | Progressive Scan | Progressive Scan | Progressive Scan |

Lens

| | | | |
|---------------|----------------|----------------|----------------|
| Focus Length | Board Lens 6mm | Board Lens 6mm | Board Lens 6mm |
| Focus Control | Fixed | Fixed | Fixed |
| Lens Type | Fixed | Fixed | Fixed |

Night Vision

| | | | |
|-------------------|------------------|------------------|------------------|
| IR Cut Filter | YES | YES | YES |
| Infrared LED | 42μ x4PCS | 42μ x4PCS | 42μ x4PCS |
| Infrared Distance | 40M | 40M | 40M |
| IR Status | AGC Auto Control | AGC Auto Control | AGC Auto Control |

Camera Features

| | | | |
|-------------------|---------------|---------------|---------------|
| Starlight | / | / | YES |
| Day/Night | YES | YES | YES |
| OSD Menu Language | YES | YES | YES |
| WDR | DWDR | DWDR | YES |
| UTC | YES | YES | YES |
| White Balance | AUTO / MANUAL | AUTO / MANUAL | AUTO / MANUAL |
| Noise Reduction | DNR | 3DNR | 3DNR |
| Gain Control | AUTO | AUTO | AUTO |

General

| | | | |
|-----------------------|--------------------------|--------------------------|--------------------------|
| Housing | IP67 | IP67 | IP67 |
| Bracket | NO | NO | NO |
| Operation Temperature | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max | -10℃ ~ +60℃ RH95% Max |
| Storage Temperature | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max | -20℃ ~ +60℃ RH95% Max |
| Power Source | DC12V±10%,750mA | DC12V±10%,750mA | DC12V±10%,750mA |
| Dimension | 162(W) x 88(H) x 86(D)mm | 162(W) x 88(H) x 86(D)mm | 162(W) x 88(H) x 86(D)mm |
| Weight | 1.4kg (with bracket) | 1.4kg (with bracket) | 1.4kg (with bracket) |

Cantonek (Guangzhou) Corporation Limited

Add.: #2 BUILDING, NO. 728 KAICHUANG AVE., ECONOMIC & TECHNOLOGICAL DEVELOPMENT ZONE, HUANGPU DISTRICT, GUANGZHOU, CHINA
 Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonek.com> Email: info@cantonek.com