



◆ SPECIFICATION

Model NO.	KBTA30HTC200FE	KBTA30HTC200F	KBTA30HTC200ESL
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps

Camera

Image Sensor	1/3" CMOS Sensor	1/2.9" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2M:1920*1080	2M:1920*1080	2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan

Lens

Focus Length	Board Lens 3.6mm	Board Lens 3.6mm	Board Lens 3.6mm
Focus Control	Fixed	Fixed	Fixed
Lens Type	Fixed	Fixed	Fixed

Night Vision

IR Cut Filter	YES	YES	YES
Infrared LED	42μ x2PCS	42μ x2PCS	42μ x2PCS
Infrared Distance	25M	25M	25M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control

Camera Features

Starlight	/	/	YES
Day/Night	YES	YES	YES
OSD Menu Language	YES	YES	YES
WDR	DWDR	DWDR	YES
UTC	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Noise Reduction	DNR	3DNR	3DNR
Gain Control	AUTO	AUTO	AUTO

General

Housing	IP67	IP67	IP67
Bracket	YES	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,500mA	DC12V±10%,500mA	DC12V±10%,500mA
Dimension	170(W) x 75(H) x 77(D)mm	170(W) x 75(H) x 77(D)mm	170(W) x 75(H) x 77(D)mm
Weight	770g	770g	770g

Cantok (guangzhou) Corporation Limited

Add.: #2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA
Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantok.com> Email: info@cantok.com