



◆ SPECIFICATION

Model NO.	KDRN20HTC200FE	KDRN20HTC200F	KDRN20HTC200ESL
Video Output Mode	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps	AHD/TVI/CVI: 2M@30fps/25fps

Camera

Image Sensor	1/3" CMOS Sensor	1/2.9" CMOS Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Image Resolution	2M:1920*1080	2M:1920*1080	2M:1920*1080
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Electronic Shutter	Auto	Auto	Auto
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan

Lens

Focus Length	Board Lens 2.8-12mm	Board Lens 2.8-12mm	Board Lens 2.8-12mm
Focus Control	Manual	Manual	Manual
Lens Type	Manual	Manual	Manual

Night Vision

IR Cut Filter	YES	YES	YES
Infrared LED	14μ x 24PCS	14μ x 24PCS	14μ x 24PCS
Infrared Distance	30M	30M	30M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control

Camera Features

Starlight	/	/	YES
Day/Night	YES	YES	YES
OSD Menu Language	YES	YES	YES
WDR	DWDR	DWDR	YES
UTC	YES	YES	YES
White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Noise Reduction	DNR	3DNR	3DNR
Gain Control	AUTO	AUTO	AUTO

General

Housing	IP67	IP67	IP67
Bracket	NO	NO	NO
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	∅ 131 x 93(H) mm	∅ 131 x 93(H) mm	∅ 131 x 93(H) mm
Weight	800g	800g	800g

Cantonk (guangzhou) Corporation Limited

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOLOGICAL DEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: info@cantonk.com