



◆ SPECIFICATION

Model NO.	KBBQ60HTC800FKP	KBBQ60HTC800ESL	KBBQ60HTC800FKE
Video Output Mode	AHD/TVI:8M@15fps,5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI: 8M@15fps/12.5fps, 4M/2M@30fps/25fps	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; CVI:8M@15fps/12.5fps,4M/2M@30fps/25fps; TVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps	AHD: 8M@15fps, 5M@20fps/12.5fps, 4M/2M@30fps/25fps; TVI/CVI: 8M@15fps/12.5fps, 5M@20fps/12.5fps 4M/2M@30fps/25fps

### Camera

Image Sensor	1/2.5" CMOS sensor	1/2.8" SONY Starvis Back-illuminated CMOS sensor	1/1.8" OmniVision CMOS sensor
Image Resolution	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 5M:2592*1944 4M:2560*1440 2M:1920*1080	8M:3840*2160 2M:1920*1080
Electronic Shutter	AUTO	AUTO	AUTO
TV System	PAL/NTSC	PAL/NTSC	PAL/NTSC
Scanning System	Progressive Scan	Progressive Scan	Progressive Scan

### Lens

Focus Length	Board Lens 2.8-12mm	Board Lens 2.8-12mm	Board Lens 2.8-12mm
Focus Control	Manual	Manual	Manual
Lens Type	Manual	Manual	Manual

### Night Vision

IR Cut Filter	YES	YES	YES
Infrared LED	42μ x4PCS	42μ x4PCS	42μ x4PCS
Infrared Distance	40M	40M	40M
IR Status	AGC Auto Control	AGC Auto Control	AGC Auto Control

### Camera Features

Starlight	/	/	/
Day/Night	YES	YES	YES/NO
OSD Menu Language	YES	YES	YES
WDR	DWDR	YES	DWDR
UTC	YES	YES	YES
Noise Reduction	3DNR	3DNR	DNR
Coaxial Audio	/	/	YES(only TVI )

White Balance	AUTO / MANUAL	AUTO / MANUAL	AUTO / MANUAL
Gain Control	AUTO	AUTO	AUTO
<b>General</b>			
Housing	IP67	IP67	IP67
Bracket	YES	YES	YES
Operation Temperature	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max	-10℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%,750mA	DC12V±10%,750mA	DC12V±10%,750mA
Dimension	211(W) x 92(H) x 90(D)mm	211(W) x 92(H) x 90(D)mm	211(W) x 92(H) x 90(D)mm
Weight	1.4Kg	1.4Kg	1.4Kg

**Cantonk (guangzhou) Corporation Limited**

Add. :2#BUILDING,NO.728 KAICHUANG AVE.,ECONOMIC&TECHNOGICALDEVELOPMENT ZONE,HUANGPU DISTRICT,GUANGZHOU,CHINA

Tel. No.: +86 20 66217288 Fax No.: +86 20 66217166 Homepage: <http://www.cantonk.com> Email: [info@cantonk.com](mailto:info@cantonk.com)